



About Reefervan

With over **35** years of industry experience, we manufacture and distribute a variety of quality O.E.M reefer products and van insulation kits across **North America**.

All reefer & insulation products have:

- **3 Year warranty**
- **Lowest** service and replacement parts cost guaranteed
- **Tech-friendly** design

INSULATION KITS AVAILABLE !



Contact Us



+1 888-445-4481



4-3610 Odyssey Drive,
Mississauga, Ontario, Canada
L5M 0Z9



sales@reefervan.com



www.reefervan.com



Scan the QR code to
learn more about our
reefers!

REEFER VAN



RV9E

Road & Electric Operation
115V Reefer - Direct Drive



+1 888-445-4481

RV9E Features

The **RV9E** Reefer is engineered for the North American market, delivering reliable performance for fresh or frozen applications on **small and regular wheelbase** vans.



RV9E Evaporator



RV9E Condenser

- 7800 BTU/hr Cooling Capacity
- Compressor Oil Separator
- R452A refrigerant compatible
- High cooling capacity fans
- VALEO Road Compressor
- SANDEN standby compressor
- CPR protection valve
- Automatic hot gas defrost
- Slim Cab Command
- 115V Standby voltage

RV9E Benefits

- ✓ Fast & Easy Installation
- ✓ 3-Year Warranty protection
- ✓ Superior cooling performance
- ✓ Simple temperature control in our cab command (°F / °C)
- ✓ Extended service life
- ✓ Maximize payload space with slim evaporator design
- ✓ Easy fault diagnosis through LED indicators



Quality Without the Premium Price

RV9E Specifications*

Specification	Value
Compressor	TM15 - TM15
Defrost	Hot Gas
Refrigerant	R404A (R452A)
Refrigerant Charge	3.1 LB (1.4 KG)
Standby Voltage	115V (20A)
AMP Draw (12VDC / AC)	29A / 16A
Condenser Weight	140 LB (64 KG)
Evaporator Weight	49 LB (22 KG)
Condensor Dimension	33"x 23"x 9.5" (838 x 584 x 241 mm)
Evaporator Dimension	33"x 23"x 7" (838 x 584 x 178 mm)
Air Flow	765 CFM
Vehicle Application	Low Roof
Road Cooling 35°F (2°C)	7800 BTU/H (2285 W)
Road Cooling 0°F (-18°C)	3410 BTU/H (1000 W)
Electric Cooling 35°F (2°C)	5200 BTU/H (1550 W)
Electric Cooling 0°F (-18°C)	3400 BTU/H (995 W)

*Ambient 100°F (38°C); Assume min. 3" of insulation for 35°F (2°C) and min. 4" of insulation for 0°F (-18°C) with polar walls